

## Joystick Keyboard KBD1010



### Key Features:

- Adopt RS485, RS422, RS232 Multiple Interface Control Signals. Support to connect up to 255 cameras.
- Support PELCO-D, PELCO-P, VISCA control protocol.
- Metal shell, Computer keyboard button design.
- Adopt Three-dimensional joystick to control the speed of the camera.
- Control camera rotation, zoom, aperture, focus, and other camera settings.
- LCD display in English and Chinese, Real-time display of the working status of the decoder and matrix.
- Key sound prompt function.
- Unique control code learning function. Customers can modify the control code instructions by themselves
- Any device on the RS485 bus can be set to a different protocol and baud rate.
- RS422 communication interface has automatic recovery function of short circuit overcurrent protection.
- The longest communication distance is up to 1200M (0.5MM twisted pair)。

Tel:+86-755-33288582

E-mail:claire@mingricctv.com

Web:www.minrraycam.com

Address: 5&6 Floor,Building 13-A,ZhongHaiXin Technology Park,Ganli Road,Lilang Avenue,Buji,Shenzhen 518112,China

## Specification

Parameter / Model	KBD1010
Communication Mode	RS485 Half duplex, RS422 Full duplex, RS232 Serial Port
Communication baud rate	2400bps, 4800bps, 9600bps, 19200bps
Interfaces	5PIN; RS232
Joystick	Three-dimensional (Control: up, down, left, right, rotate)
Display Mode	LCD Blue Screen Display
Power Supply	DC12V $\pm$ 10%
Power Consumption	6W MAX
Working Temperature	-10°C $\sim$ 50°C
Storage Temperature	$\leq$ 90%RH(No frosting)
Dimensions	320mm (L) X179.3mm (W) X106.4mm(H)

## Dimension(unit: mm)

